(19) World Intellectual Property Organization

International Bureau



1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 - 1860 -

(43) International Publication Date 27 January 2005 (27.01.2005)

PCT

(10) International Publication Number WO 2005/008307 A2

- (51) International Patent Classification7: G02B 6/44, 6/50
- (21) International Application Number:

PCT/CA2004/001043

- (22) International Filing Date: 16 July 2004 (16.07.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/487,595

17 July 2003 (17.07.2003) US

- (71) Applicant (for all designated States except US): TERAS-PAN NETWORKS INC. [CA/CA]; Suite 500, 134 Abbott Street, Vancouver, British Columbia V6B 2K4 (CA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): DOFHER, Darren [CA/CA]; 2130 Grant Avenue, Port Coquitlam, British Columbia V3B 1R2 (CA).
- (74) Agent: RIDOUT & MAYBEE LLP; 150 Metcalfe Street, 19th Floor, Ottawa, Ontario K2P 1P1 (CA).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SURFACE INLAID FIBRE OPTIC NETWORK INSTALLATIONS



(57) Abstract: A system for protecting buried optic fibre nodes which permits surface inlay installation of cable without the need to expose free ends of the cable for threading through any apertures, includes a protective housing composed of spaced apart panels which define an interior space. The panels open to expose the interior for installation of a length of cable therein. An insert fits within the space, which includes a channel which is exposed when the panels open for insertion of a cable. The insert includes a void to receive a cable junction box. A removable protective outer casing may be provided, either in the form of a pair of outer walls with a removable cap or base, or a can-like container having a removable top and two or more opposed slots communicating with the upper rim of the container. The housing fits within the container, with the cable entering and exiting through the slots, which also permit a saw cut to pass through the slots to facilitate installation of the system. The system also includes a pre-assembled cable network including nodes, cable and housings that may be buried within trenches cut into a surface.

WO 2005/008307 A2 | INDIAN IND

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.